



JCB MOBILE SCISSOR TABLE



TECHNICAL FEATURES

- Safe, light, easy to use and highly manoeuvrable
- High quality robust construction
- A range of maximum lift heights from 750mm to 1610mm
- Manual operation
- Single or double lifts available
- Heavy duty arm, bearings and hydraulics
- All wheels are fitted with sealed bearings and polyurethane tyres
- One castor fitted with a total stop brake as standard
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN 1570 and BS:5323:1980

CAPACITY	LIFT HEIGHT	PLATFORM DIMENSIONS	OVERALL DIMENSIONS	OWN WEIGHT	CODE
200kg	255 - 765mm	485 x 700mm	485 x 910mm	42kg	BD-SC-200-S-M-JCB
300kg	310 - 860mm	520 x 850mm	520 x 930mm	80kg	BD-SC-300-S-M-JCB
500kg	330 - 950mm	610 - 920mm	610 x 1030mm	150kg	BD-SC-500-S-M-JCB
800kg	345 - 940mm	610 x 920mm	610 x 1030mm	120kg	BD-SC-800-S-M-JCB
350kg	425 - 1620mm	610 x 920mm	610 x 1030mm	150kg	BD-SC-350-D-M-JCB