



LIGHT DUTY SCISSOR LIFT



- The 150kg scissor tables are light, portable, highly manoeuvrable and easy to use.
- Available in super lightweight aluminium or steel
- Lifts to a height of 780mm
- Folds flat for easy transportation and storage
- Hinged handle automatically locks into upright position, released by foot bar
- Manual operation
- Particularly suited to office and pharmaceutical environments
- Optional extras are available such as a roller top or bellows skirt
- Quality British manufacture and design
- Manufactured to conform to EU Standards BSEN 1570 and BS:5323:1980

TECHNICAL FEATURES

- Can be used safely at any height
- Fitted with a total stop brake as standard to prevent the table from moving when being unloaded
- Unique lift up table top allows safe and easy maintenance- can only be lifted when table in a closed position
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- Rubber non-marking tyres to prevent damage to floors
- Wheels fitted with thread guards
- Epoxy powder coated finish for durability
- Issued with a test certificate

WARNINGS

- Scissor tables are NOT designed to carry people- special safety features would be required in accordance with EN1570
- Tables which carry wheeled loads or rolling loads must be fitted with a device to prevent these rolling off
- Mobile tables are designed to be propelled by pedestrians, if any other means are to be used please use precautions in accordance with EN1570
- The rated load of the table must not be exceeded as this can cause damage to the table. The load must be evenly distributed on the table surface for stability.



TECHNICAL SPECIFICATION

Model	C Raised Height	B Closed Height	E x A Platform W x L	E x D O/A W x L	F Handle Height	Wheel Dia	Approx Weight (KG)	Reference	Approx Pumps to Lift Height
STEEL	780	255	450 x 760	450 x 990	940	125	41	SC-150-S-M	14
ALUMINIUM	780	255	450 x 760	450 x 990	940	125	27	SC-150-S-M- ALU-PC	14

All dimensions are in mm unless otherwise shown

Options

- Second Braked wheel
- Stainless Steel top cover
- Plastic roller conveyor top (Increases closed/raised height by 60mm)
- Ball top
- Bellows safety skirt
- Rubber Mat

