



MEDIUM DUTY SCISSOR LIFT



- Safe, light, easy to use and highly manoeuvrable
- High quality robust construction
- A range of maximum lift heights from 840mm to 1550mm
- Manual or battery electric operation
- Optional extras from stainless steel lid to bellows skirt
- Quality British design and manufacture

TECHNICAL FEATURES

ALL MODELS

- Single or double lifts available
- Heavy duty arm, bearings and hydraulics
- All wheels are fitted with sealed bearings and polyurethane tyres
- 2 swivel castors fitted with a total stop brake as standard
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- A unique lift up table top allows safe and easy maintenance- can only be lifted when table is in a closed position
- Each table is issued with operating instructions and a test certificate in conformance with EU Standards EN 1570 and BS:5323:1980

BATTERY ELECTRIC MODELS

- Models include 12v traction battery and charger
- Safety cut-off bar fitted to the underside of the platform stops table from lowering in the case of an obstruction
- Remote push button control up/down operation
- Emergency stop switch
- Safe design plug-in charger
- Strong electrical flex
- Electrical contacts/motors conform to EQ1570/ EN 60529



TECHNICAL SPECIFICATION

SINGLE SCISSOR TABLES

| Capacity | C Raised Height | B Closed Height | Operation | E x A Platform W x L | E x D O/A W x L | F Handle Height | Wheel Dia | Approx Weight | Reference | Approx Lifting Time |
|----------|-----------------|-----------------|------------------|----------------------|-----------------|-----------------|-----------|---------------|------------|---------------------|
| 300KG | 840 | 335 | Manual | 500 x 840 | 500 x 1050 | 860 | 125 | 83 | SC-300-S-M | 18 pumps |
| 300KG | 840 | 335 | Battery Electric | 500 x 840 | 500 x 1130 | 860 | 125 | 130 | SC-300-S-E | 9 seconds |
| 500KG | 900 | 340 | Manual | 610 x 1030 | 610 x 1320 | 925 | 125 | 109 | SC-500-S-M | 40 pumps |
| 500KG | 900 | 340 | Battery Electric | 610 x 1030 | 610 x 1330 | 925 | 125 | 158 | SC-500-S-E | 12 seconds |

DOUBLE SCISSOR TABLES

| Capacity | C Raised Height | B Closed Height | Operation | E x A Platform W x L | E x D O/A W x L | F Handle Height | Wheel Dia | Approx Weight | Reference | Approx Lifting Time |
|----------|-----------------|-----------------|------------------|----------------------|-----------------|-----------------|-----------|---------------|------------|---------------------|
| 125KG | 1420 | 430 | Manual Hyd | 500 x 840 | 500 x 1090 | 860 | 125 | 100 | SC-125-D-M | 19 pumps |
| 125KG | 1420 | 430 | Battery Electric | 500 x 840 | 500 x 1130 | 860 | 125 | 147 | SC-125-D-E | 9 seconds |
| 300KG | 1350 | 295 | Manual Hyd | 590 x 840 | 640 x 1190 | 900 | 150/125 | 110 | SC-300-D-M | 25 pumps |
| 300KG | 1350 | 295 | Battery Electric | 590 x 840 | 640 x 1190 | 900 | 150/125 | 147 | SC-300-D-E | 15 seconds |
| 450KG | 1550 | 295 | Manual Hyd | 610 x 1030 | 665 x 1350 | 910 | 150/125 | 143 | SC-450-D-M | 71 pumps |
| 450KG | 1550 | 295 | Battery Electric | 610 x 1030 | 665 x 1350 | 910 | 150/125 | 190 | SC-450-D-E | 26 seconds |

All dimensions are in mm unless otherwise shown

Options

- Stainless steel top cover
- Plastic roller conveyor top (Increases closed / raised height by 60)
- Ball Top
- Bellows safety skirt
- Rubber Mat

