Data Sheet



The Pallet Changer is specifically designed to transfer palletized loads without manual handling of the pallet itself.

It will accommodate pallets up to 1200mm in either direction with a height range of 2.0m down to 600mm. Totally automated, it represents the most advanced form of pallet exchange in our range.

The Pallet Changer is best suited to boxed or cluster-packed product and is equally effective with tubs, drums and reels.

PALLET CHANGER








USES INCLUDE

- Load transfer from wood to hygienic in-house pallets
- Switching outgoing loads to shipping or expendable pallets
- Handling loads which must remain the original way up after transfer

KEY FEATURES

- Pallet gripping system adapts automatically to all normal sizes
- Side retaining walls with optical sensors or pressure option
- Flush-to-floor loading no ramp
- 1500kgs loading capacity.
- Smooth and effective auto-operation allowing 25 pallet per hour throughput
 - Not recommended for bagged goods or thin-layered product
- Price inclusive of full guarding system

METHOD OF OPERATION





1

2

3

4

and

5


6

7


PALLET CHANGER Specifications

Usable		Max 2050mr
Jaw Opening		Min 600mr
	L	arger jaw opening models can be bui
Standard		Width 1300mr
Load Table		Depth 1200mr
Loading Capacity		1500 kg
Power Supply		3ph / 400V / 32 am
Motor Size		4k\
Weight		1800 kg
Weight of standa	rd guards	210 kg
Controls	Fully-automated single touch push but	ton control with manual overrid
Actual		Width 2.16r
Operating		Depth 3.35r
Space		Height 2.75r
Operating Space		A Width 3.03r
Including		B Depth 4.82r
Standard Guards		C Height 2.75r
]	Width 2.16r
Standard Shipping		
Standard Shipping Dimensions		Depth 2.45r

SIDE ELEVATION



PLAN VIEW



DEPTH B



Gressenhall Dereham Norfolk NR20 4DT Tel : +44 (0)1362 861066 Email : sales@premierpal.co.uk Web : www.premierpal.co.uk