CE

Organismo Notificato n. 0302

AGENZIA NAZIONALE CERTIFICAZIONE COMPONENTI E PRODOTTI 20134 MILANO - VIG Rombon, 11



www.ancep.it ancep@ancep.it

Tel. ++39.(0)2.210407.1 r.a. Fax ++39.(0)2.210407218

EC TYPE EXAMINATION CERTIFICATE

n° DPI 303 AT 1228

PERSONAL PROTECTIVE EQUIPMENT Directive 89/686/CEE

Denomination:

WORK POSITIONING LANYARD

Type:

A04ECO1

Category:

IIIa PPE submitted to quality control system for the final product (89/686/EEC art. 11a/11b)

Applicant:

CARABELLI S.r.l. - Via del Lavoro, 3 - 20083 Gaggiano (MI) - ITALY

HAVING ASCERTAINED

- that the technical documentation submitted by the above firm together with the above-mentioned application has proved upon examination to be in order.
- the positive results of the checks and tests performed by this Agency, on the sample representative of production,

Having ascertained that the documentation and the representative model comply with the requirements of the standard:

EN 358:1999

WE HEREBY CERTIFY

that the model of Individual Protective Device of the above-mentioned type and category over mentioned complies with the documentation produced and with the essential health and safety requirements as stated in EEC Directive 89/686.

issue date:

01.06.2010

Review date:

01.00.2

GENERAL MANAGER Ing. G. Gazzerro

page 1 of 2



EC type examination certificate n° DPI 303 AT 1228


Personal Protective Equipment - Directive 89/686/CEE

Basic type description:

Code A04ECO1

Work positioning lanyard adjustable to maximum 2 metres, made of:

- rope made of three-strand polyamide fibre, diameter 16 mm
- steel automatic length adjuster with triangular steel connector with automatic twist lock EN 362:2004 Class A
- steel hook connector with a double safety device EN 362:2004 Class A/T
- aluminium travel end clamp
- sewing end of rope
- threads polyamide 6.6 colour yellow



Variations description:

Code A04P16AA

As basic type, with:

- tubular protection sleeve made of PVC coated fabric colour red

Code A04P16AL

As basic type, with:

- aluminium alloy automatic length adjuster with triangular aluminium alloy connector with automatic twist lock EN 362:2004 Class A
- aluminium alloy hook connector with a double safety device EN 362:2004 Class A/T
- tubular protection sleeve made of PVC coated fabric colour red

Sizes:

= =

Standards:

EN 358:1999

Personal protective equipment for work positioning and prevention of falls from a height-Belts for work positioning and restraint and work positioning

lanyards

Performance level:

==

Proper use:

The equipment can be used as component to connect a waist belt to an

anchor point, or to a structure by encircling it, as a means of support.

The equipment is not suitable for other uses.

Issue date:

01.06.2010

Review date:

_

GENERAL MANAGER Ing. G. Gazzerro